

# Material Safety Data Sheet

## Tuscan Stoneworx Accessories

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

DATE ISSUED: March 1, 2010  
REVIEWED ON: March 29, 2010  
REVISION: FORMAT

#### PRODUCTS COVERED BY THIS MSDS:

- Tuscan Stoneworx Color Wash
  - Chocolate Brown
  - Midnight Black
  - Exotic Blue
  - Forest Green
  - Winter White
  - Golden Yellow
  - Burnt Red
  - Earth Brown
  - Rambling Rose
  - Sunrise Yellow
  - Lemon Yellow
  - Siren Red

#### COMPANY CONTACT INFORMATION:

**Tuscan Stoneworx USA, LLC**  
165 North 1330 West, C-4  
Orem, UT 84057  
Phone: (888) 368-9494  
Fax: (801) 734-6959  
[www.tuscanstoneworx.com](http://www.tuscanstoneworx.com)

### SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

#### CHOCOLATE BROWN

Ingredient	% Wt	CAS #	OSHA PEL	ACGIH TLV
Ethylene Glycol	16	107-21-1	100 mg/m <sup>3</sup> Ceiling	50 ppm Ceiling
Octylphenoxypoly (ethoxy) ethanol	8	9036-19-5	Not Available	Not Available
Talc	9	14807-96-6	2 mg/m <sup>3</sup> as Resp. Dust	2 mg/m <sup>3</sup> as Resp. Dust
Carbon Black	2	1333-86-4	3.5 mg/m <sup>3</sup>	3.5 mg/m <sup>3</sup>

#### MIDNIGHT BLACK

Ingredient	% Wt	CAS #	OSHA PEL	ACGIH TLV
Ethylene Glycol	25	107-21-1	100 mg/m <sup>3</sup> Ceiling	50 ppm Ceiling
Octylphenoxypoly (ethoxy) ethanol	7	9036-19-5	Not Available	Not Available
Talc	29	14807-96-6	2 mg/m <sup>3</sup> as Resp. Dust	2 mg/m <sup>3</sup> as Resp. Dust
Quartz	.1	14808-60-7	0.025 mg/m <sup>3</sup> Resp. Dust	0.1 mg/m <sup>3</sup> Resp. Dust
Carbon Black	2	1333-86-4	3.5 mg/m <sup>3</sup>	3.5 mg/m <sup>3</sup>

**EXOTIC BLUE**

Ingredient	% Wt	CAS #	OSHA PEL	ACGIH TLV
Ethylene Glycol	23	107-21-1	100 mg/m <sup>3</sup> Ceiling	50 ppm Ceiling
Octylphenoxypoly (ethoxy) ethanol	6	9036-19-5	Not Available	Not Available
Talc	35	14807-96-6	2 mg/m <sup>3</sup> as Resp. Dust	2 mg/m <sup>3</sup> as Resp. Dust
Quartz	.2	14808-60-7	0.025 mg/m <sup>3</sup> Resp. Dust	0.1 mg/m <sup>3</sup> Resp. Dust

**FOREST GREEN**

Ingredient	% Wt	CAS #	OSHA PEL	ACGIH TLV
Ethylene Glycol	24	107-21-1	100 mg/m <sup>3</sup> Ceiling	50 ppm Ceiling
Octylphenoxypoly (ethoxy) ethanol	13	9036-19-5	Not Available	Not Available
Talc	23	14807-96-6	2 mg/m <sup>3</sup> as Resp. Dust	2 mg/m <sup>3</sup> as Resp. Dust
Quartz	.1	14808-60-7	0.025 mg/m <sup>3</sup> Resp. Dust	0.1 mg/m <sup>3</sup> Resp. Dust

**WINTER WHITE**

Ingredient	% Wt	CAS #	OSHA PEL	ACGIH TLV
Ethylene Glycol	15	107-21-1	100 mg/m <sup>3</sup> Ceiling	50 ppm Ceiling
Octylphenoxypoly (ethoxy) ethanol	6	9036-19-5	Not Available	Not Available
Talc	9	14807-96-6	2 mg/m <sup>3</sup> as Resp. Dust	2 mg/m <sup>3</sup> as Resp. Dust
Titanium Dioxide	52	13463-67-7	5 mg/m <sup>3</sup> Resp. Fraction 10 mg/m <sup>3</sup> Total Dust	10 mg/m <sup>3</sup> as Dust

**GOLDEN YELLOW**

Ingredient	% Wt	CAS #	OSHA PEL	ACGIH TLV
Ethylene Glycol	12	107-21-1	100 mg/m <sup>3</sup> Ceiling	50 ppm Ceiling
Octylphenoxypoly (ethoxy) ethanol	9	9036-19-5	Not Available	Not Available

**BURNT RED**

Ingredient	% Wt	CAS #	OSHA PEL	ACGIH TLV
Ethylene Glycol	14	107-21-1	100 mg/m <sup>3</sup> Ceiling	50 ppm Ceiling
Octylphenoxypoly (ethoxy) ethanol	3	9036-19-5	Not Available	Not Available
Talc	4	14807-96-6	2 mg/m <sup>3</sup> as Resp. Dust	2 mg/m <sup>3</sup> as Resp. Dust

**EARTH BROWN**

Ingredient	% Wt	CAS #	OSHA PEL	ACGIH TLV
Ethylene Glycol	14	107-21-1	100 mg/m <sup>3</sup> Ceiling	50 ppm Ceiling
Octylphenoxypoly (ethoxy) ethanol	3	9036-19-5	Not Available	Not Available
Talc	4	14807-96-6	2 mg/m <sup>3</sup> as Resp. Dust	2 mg/m <sup>3</sup> as Resp. Dust
Titanium White	.1	13463-67-7	10 mg/m <sup>3</sup> Total Dust 5 mg/m <sup>3</sup> Resp. Fraction	10 mg/m <sup>3</sup> as Dust
Carbon Black	.2	1333-86-4	3.5 mg/m <sup>3</sup>	3.5 mg/m <sup>3</sup>

**RAMBLING ROSE**

Ingredient	% Wt	CAS #	OSHA PEL	ACGIH TLV
Ethylene Glycol	27	107-21-1	100 mg/m <sup>3</sup> Ceiling	50 ppm Ceiling
Octylphenoxypoly (ethoxy) ethanol	6	9036-19-5	Not Available	Not Available
Talc	18	14807-96-6	2 mg/m <sup>3</sup> as Resp. Dust	2 mg/m <sup>3</sup> as Resp. Dust

**SUNRISE YELLOW**

Ingredient	% Wt	CAS #	OSHA PEL	ACGIH TLV
Ethylene Glycol	20	107-21-1	100 mg/m <sup>3</sup> Ceiling	50 ppm Ceiling
Octylphenoxy poly (ethoxy) ethanol	12	9036-19-5	Not Available	Not Available
Talc	10	14807-96-6	2 mg/m <sup>3</sup> as Resp. Dust	2 mg/m <sup>3</sup> as Resp. Dust

**LEMON YELLOW**

Ingredient	% Wt	CAS #	OSHA PEL	ACGIH TLV
Ethylene Glycol	20	107-21-1	100 mg/m <sup>3</sup> Ceiling	50 ppm Ceiling
Octylphenoxy poly (ethoxy) ethanol	13	9036-19-5	Not Available	Not Available
Talc	24	14807-96-6	2 mg/m <sup>3</sup> as Resp. Dust	2 mg/m <sup>3</sup> as Resp. Dust
Quartz	.1	14808-60-7	0.025 mg/m <sup>3</sup> Resp. Dust	0.1 mg/m <sup>3</sup> Resp. Dust

**SIREN RED**

Ingredient	% Wt	CAS #	OSHA PEL	ACGIH TLV
Ethylene Glycol	31	107-21-1	100 mg/m <sup>3</sup> Ceiling	50 ppm Ceiling
Octylphenoxy poly (ethoxy) ethanol	8	9036-19-5	Not Available	Not Available
Talc	9	14807-96-6	2 mg/m <sup>3</sup> as Resp. Dust	2 mg/m <sup>3</sup> as Resp. Dust

**SECTION 3: HAZARDS IDENTIFICATION**

**ROUTES OF EXPOSURE**

**INHALATION:** of vapor or spray mist.

**EYE OR SKIN:** contact with the product, vapor, or spray mist.

**EFFECTS OF OVEREXPOSURE**

**EYES:** Irritation.

**SKIN:** Prolonged or repeated exposure may cause irritation.

**INHALATION:** Irritation of the upper respiratory system. In a confined area vapors in high concentration may cause headache, nausea or dizziness. Prolonged over exposure to solvent ingredients in Section 2 may cause adverse effects to the liver and urinary system.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** None generally recognized.

**CANCER INFORMATION:** For complete discussion of toxicology data refer to Section 11.

**HMIS CODES:** (0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Sever)

**CHOCOLATE BROWN**

Fire: 0  
 Health: 2  
 Reactivity: 0

**MIDNIGHT BLACK**

Fire: 1  
 Health: 2  
 Reactivity: 0

**EXOTIC BLUE**

Fire: 1  
 Health: 2  
 Reactivity: 0

**FOREST GREEN**

Fire: 1

Health:	2
Reactivity:	0
<b>WINTER WHITE</b>	
Fire:	0
Health:	2
Reactivity:	0
<b>GOLDEN YELLOW</b>	
Fire:	0
Health:	2
Reactivity:	0
<b>BURNT RED</b>	
Fire:	0
Health:	2
Reactivity:	0
<b>EARTH BROWN</b>	
Fire:	0
Health:	2
Reactivity:	0
<b>RAMBLING ROSE</b>	
Fire:	0
Health:	2
Reactivity:	0
<b>SUNRISE YELLOW</b>	
Fire:	0
Health:	2
Reactivity:	0
<b>LEMON YELLOW</b>	
Fire:	1
Health:	2
Reactivity:	0
<b>SIREN RED</b>	
Fire:	1
Health:	2
Reactivity:	0

---

#### SECTION 4: FIRST AID MEASURES

**EYES:** Flush eyes with water, lifting eyelids periodically. Remove contact lenses. Continue flushing for 15 minutes or until eyes return to normal. Get medical attention.

**SKIN:** Wash with soap and water. Get medical attention if irritation develops or persists. Wash clothing before re-use.

**INGESTION:** DO NOT INDUCE VOMITING, contact medical personnel or poison control center immediately.

**INHALATION:** If affected, remove from area to fresh air. Restore breathing, while keeping warm and quiet. Get medical attention for any breathing difficulty.

---

#### SECTION 5: FIRE FIGHTING MEASURES

##### CAUTION: FLAMMABLE PROPERTIES

##### CHOCOLATE BROWN

Flammable Class:	N/A
Flash Point:	N/A
LEL:	N/A
UEL:	N/A

**MIDNIGHT BLACK**

Flammable Class: N/A  
Flash Point: >200°F (93.3°C) PMCC  
LEL: N/A  
UEL: N/A

**EXOTIC BLUE**

Flammable Class: N/A  
Flash Point: >200°F (93.3°C) PMCC  
LEL: N/A  
UEL: N/A

**FOREST GREEN**

Flammable Class: N/A  
Flash Point: >200°F (93.3°C) PMCC  
LEL: N/A  
UEL: N/A

**WINTER WHITE**

Flammable Class: N/A  
Flash Point: N/A  
LEL: N/A  
UEL: N/A

**GOLDEN YELLOW**

Flammable Class: N/A  
Flash Point: N/A  
LEL: N/A  
UEL: N/A

**BURNT RED**

Flammable Class: N/A  
Flash Point: N/A  
LEL: N/A  
UEL: N/A

**EARTH BROWN**

Flammable Class: N/A  
Flash Point: N/A  
LEL: N/A  
UEL: N/A

**RAMBLING ROSE**

Flammable Class: N/A  
Flash Point: N/A  
LEL: N/A  
UEL: N/A

**SUNRISE YELLOW**

Flammable Class: N/A  
Flash Point: N/A  
LEL: N/A  
UEL: N/A

**LEMON YELLOW**

Flammable Class: N/A  
Flash Point: >200°F (93.3°C) PMCC  
LEL: N/A  
UEL: N/A

**SIREN RED**

Flammable Class: N/A  
Flash Point: >200°F (93.3°C) PMCC  
LEL: N/A  
UEL: N/A

**EXTINGUISHING AGENTS:** Carbon Dioxide (CO<sub>2</sub>), Dry Chemical, or Alcohol Foam  
**UNUSUAL FIRE FIGHTING PROCEDURES:** Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

**SPECIAL FIRE FIGHTING PROCEDURES:** Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible auto-ignition or explosion when exposed to extreme heat.

---

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**STEPS TO TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Remove all sources of ignition, ventilate the area, and remove with an inert absorbent.

---

## SECTION 7: HANDLING & STORAGE

**STORAGE CATEGORY:** DOL Storage Class IIIB

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:** Keep container closed when not in use. Transfer only in approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

**STORAGE CATEGORY:** Not applicable

---

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

**PRECAUTIONS TO BE TAKEN IN USE:** Use only with adequate ventilation. Avoid contact with skin and eyes. Avoid breathing vapor and spray mist. Wash hands after using. This coating may contain materials classified as nuisance particulates (listed “as Dust” in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m<sup>3</sup> (total dust), 3 mg/m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction).

**VENTILATION:** Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

**SKIN:** Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

**RESPIRATORY PROTECTION:** If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2. When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

**EYE:** Wear safety spectacles with un-perforated side-shields.

---

## SECTION 9: PHYSICAL & CHEMICAL PROPERTIES

### CHOCOLATE BROWN

Product Weight: ..... 14.12 lb/gal (1692 g/l)  
Specific Gravity: ..... 1.70  
Boiling Point: ..... 212-388°F (100-197°C)  
Melting Point: ..... Not Available  
Volatile Volume: ..... 59%  
Evaporation Rate: ..... Slower than ether  
Vapor Density: ..... Heavier than air  
Solubility in Water: ..... N/A  
pH: ..... 8.0  
Volatile Organic Compounds (VOC Theoretical – As Packaged)

---

3.48 lb/gal (417 g/l).....Less Water and Federally Exempt Solvents  
(Chocolate Cont'd)  
2.26 lb/gal (270 g/l).....Emitted VOC

**MIDNIGHT BLACK**

Product Weight: ..... 11.31 lb/gal (1354 g/l)  
Specific Gravity: ..... 1.36  
Boiling Point: ..... 212-388°F (100-197°C)  
Melting Point: ..... Not Available  
Volatile Volume: ..... 63%  
Evaporation Rate:..... Slower than ether  
Vapor Density: ..... Heavier than air  
Solubility in Water: ..... N/A  
pH:..... 8.0  
Volatile Organic Compounds (VOC Theoretical – As Packaged)  
4.23 lb/gal (507 g/l).....Less Water and Federally Exempt Solvents  
2.85 lb/gal (342 g/l).....Emitted VOC

**EXOTIC BLUE**

Product Weight: ..... 11.60 lb/gal (1389 g/l)  
Specific Gravity: ..... 1.40  
Boiling Point: ..... 212-388°F (100-197°C)  
Melting Point: ..... Not Available  
Volatile Volume: ..... 61%  
Evaporation Rate:..... Slower than ether  
Vapor Density: ..... Heavier than air  
Solubility in Water: ..... N/A  
pH:..... 6.9  
Volatile Organic Compounds (VOC Theoretical – As Packaged)  
3.98 lb/gal (477 g/l).....Less Water and Federally Exempt Solvents  
2.72 lb/gal (326 g/l).....Emitted VOC

**FOREST GREEN**

Product Weight: ..... 11.02 lb/gal (1320 g/l)  
Specific Gravity: ..... 1.33  
Boiling Point: ..... 212-388°F (100-197°C)  
Melting Point: ..... Not Available  
Volatile Volume: ..... 59%  
Evaporation Rate:..... Slower than ether  
Vapor Density: ..... Heavier than air  
Solubility in Water: ..... N/A  
pH:..... 7.0  
Volatile Organic Compounds (VOC Theoretical – As Packaged)  
3.84 lb/gal (460 g/l).....Less Water and Federally Exempt Solvents  
2.63 lb/gal (315 g/l).....Emitted VOC

**WINTER WHITE**

Product Weight: ..... 15.57 lb/gal (1865 g/l)  
Specific Gravity: ..... 1.87  
Boiling Point: ..... 212-388°F (100-197°C)  
Melting Point: ..... Not Available  
Volatile Volume: ..... 53%  
Evaporation Rate:..... Slower than ether  
Vapor Density: ..... Heavier than air  
Solubility in Water: ..... N/A





(Winter White Cont'd)

pH:.....8.0  
Volatile Organic Compounds (VOC Theoretical – As Packaged)  
3.23 lb/gal (387 g/l).....Less Water and Federally Exempt Solvents  
2.30 lb/gal (275 g/l).....Emitted VOC

**GOLDEN YELLOW**

Product Weight: ..... 15.30 lb/gal (1833 g/l)  
Specific Gravity: ..... 1.84  
Boiling Point: ..... 212-388°F (100-197°C)  
Melting Point: ..... Not Available  
Volatile Volume: ..... 54%  
Evaporation Rate: ..... Slower than ether  
Vapor Density: ..... Heavier than air  
Solubility in Water: ..... N/A  
pH:..... 7.5  
Volatile Organic Compounds (VOC Theoretical – As Packaged)  
2.80 lb/gal (335 g/l).....Less Water and Federally Exempt Solvents  
1.81 lb/gal (217 g/l).....Emitted VOC

**BURNT RED**

Product Weight: ..... 17.58 lb/gal (2106 g/l)  
Specific Gravity: ..... 2.12  
Boiling Point: ..... 212-388°F (100-197°C)  
Melting Point: ..... Not Available  
Volatile Volume: ..... 62%  
Evaporation Rate: ..... Slower than ether  
Vapor Density: ..... Heavier than air  
Solubility in Water: ..... N/A  
pH:..... 8.5  
Volatile Organic Compounds (VOC Theoretical – As Packaged)  
3.89 lb/gal (466 g/l).....Less Water and Federally Exempt Solvents  
2.55 lb/gal (306 g/l).....Emitted VOC

**EARTH BROWN**

Product Weight: ..... 11.63 lb/gal (1393 g/l)  
Specific Gravity: ..... 1.40  
Boiling Point: ..... 212-388°F (100-197°C)  
Melting Point: ..... Not Available  
Volatile Volume: ..... 65%  
Evaporation Rate: ..... Slower than ether  
Vapor Density: ..... Heavier than air  
Solubility in Water: ..... N/A  
pH:..... 7.0  
Volatile Organic Compounds (VOC Theoretical – As Packaged)  
4.39 lb/gal (526 g/l).....Less Water and Federally Exempt Solvents  
2.87 lb/gal (344 g/l).....Emitted VOC

**RAMBLING ROSE**

Product Weight: ..... 10.35 lb/gal (1239 g/l)  
Specific Gravity: ..... 1.25  
Boiling Point: ..... 212-388°F (100-197°C)  
Melting Point: ..... Not Available  
Volatile Volume: ..... 67%  
Evaporation Rate: ..... Slower than ether





Vapor Density: .....Heavier than air  
Solubility in Water: .....N/A  
pH:.....8.0  
Volatile Organic Compounds (VOC Theoretical – As Packaged)  
4.54 lb/gal (544 g/l).....Less Water and Federally Exempt Solvents  
2.86 lb/gal (343 g/l).....Emitted VOC

**SUNRISE YELLOW**

Product Weight: .....10.47 lb/gal (1254 g/l)  
Specific Gravity: .....1.26  
Boiling Point: .....212-388°F (100-197°C)  
Melting Point: .....Not Available  
Volatile Volume:.....48%  
Evaporation Rate:.....Slower than ether  
Vapor Density: .....Heavier than air  
Solubility in Water: .....N/A  
pH:.....8.0  
Volatile Organic Compounds (VOC Theoretical – As Packaged)  
2.89 lb/gal (346 g/l).....Less Water and Federally Exempt Solvents  
2.15 lb/gal (258 g/l).....Emitted VOC

**LEMON YELLOW**

Product Weight: .....11.05 lb/gal (1324 g/l)  
Specific Gravity: .....1.33  
Boiling Point: .....212-388°F (100-197°C)  
Melting Point: .....Not Available  
Volatile Volume:.....54%  
Evaporation Rate:.....Slower than ether  
Vapor Density: .....Heavier than air  
Solubility in Water: .....N/A  
pH:.....7.0  
Volatile Organic Compounds (VOC Theoretical – As Packaged)  
3.22 lb/gal (386 g/l).....Less Water and Federally Exempt Solvents  
2.26 lb/gal (271 g/l).....Emitted VOC

**SIREN RED**

Product Weight: .....9.73 lb/gal (1165 g/l)  
Specific Gravity: .....1.17  
Boiling Point: .....212-388°F (100-197°C)  
Melting Point: .....Not Available  
Volatile Volume:.....66%  
Evaporation Rate:.....Slower than ether  
Vapor Density: .....Heavier than air  
Solubility in Water: .....N/A  
pH:.....6.5  
Volatile Organic Compounds (VOC Theoretical – As Packaged)  
4.63 lb/gal (555 g/l).....Less Water and Federally Exempt Solvents  
3.10 lb/gal (372 g/l).....Emitted VOC

---

**SECTION 10: STABILITY & REACTIVITY**

**STABILITY:** Stable

**CONDITIONS TO AVOID:** None Known

**INCOMPATIBILITY:** None Known

**HAZARDOUS DECOMPOSITION PRODUCTS:** By Fire: Carbon Dioxide (CO<sub>2</sub>) and Carbon Monoxide (CO).

**HAZARDOUS POLYMERIZATION:** Will not occur.

**SECTION 11: TOXICOLOGICAL INFORMATION****CHRONIC HEALTH HAZARDS:**

**Carbon Black** is classified by IARC as possibly carcinogenic to humans (group 2B) based on experimental animal data; however, there is insufficient evidence in humans for its carcinogenicity.

**Ethylene Glycol** is considered an animal tetratogen. It has been shown to cause birth defects in rats and mice at high doses when given in drinking water or by gavage. There is no evidence to indicate it causes birth defects in humans.

**Crystalline Silica (Quartz, Cristobalite)** is listed by IARC and NTP. Long term exposure to high levels of silica dust, which can occur only when sanding or abrading the dry film, may cause lung damage (silicosis) and possibly cancer.

**Titanium Dioxide**, IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to *titanium dioxide* but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to *titanium dioxide* is thought to occur during the use of products in which *titanium* is bound to other materials, such as paint."

**CHOCOLATE BROWN**

Ingredient Name	CAS #	LC50 Rat (4hr)	LD50 Rat
Ethylene Glycol	107-21-1	Not Available	4700 mg/kg
Octylphenoxy poly (ethoxy) ethanol	9036-19-5	Not Available	Not Available
Talc	14807-96-6	Not Available	Not Available
Carbon Black	1333-86-4	Not Available	Not Available

**MIDNIGHT BLACK**

Ingredient Name	CAS #	LC50 Rat (4hr)	LD50 Rat
Ethylene Glycol	107-21-1	Not Available	4700 mg/kg
Octylphenoxy poly (ethoxy) ethanol	9036-19-5	Not Available	Not Available
Quartz	14808-60-7	Not Available	Not Available
Talc	14807-96-6	Not Available	Not Available
Carbon Black	1333-86-4	Not Available	Not Available

**EXOTIC BLUE**

Ingredient Name	CAS #	LC50 Rat (4hr)	LD50 Rat
Ethylene Glycol	107-21-1	Not Available	4700 mg/kg
Octylphenoxy poly (ethoxy) ethanol	9036-19-5	Not Available	Not Available
Talc	14807-96-6	Not Available	Not Available
Quartz	14808-60-7	Not Available	Not Available

**FOREST GREEN**

Ingredient Name	CAS #	LC50 Rat (4hr)	LD50 Rat
Ethylene Glycol	107-21-1	Not Available	4700 mg/kg
Octylphenoxy poly (ethoxy) ethanol	9036-19-5	Not Available	Not Available
Talc	14807-96-6	Not Available	Not Available
Quartz	14808-60-7	Not Available	Not Available

**WINTER WHITE**

Ingredient Name	CAS #	LC50 Rat (4hr)	LD50 Rat
Ethylene Glycol	107-21-1	Not Available	4700 mg/kg

Octylphenoxypoly (ethoxy) ethanol	9036-19-5	Not Available	Not Available
Talc	14807-96-6	Not Available	Not Available
Titanium Dioxide	13463-67-7	Not Available	Not Available

**GOLDEN YELLOW**

Ingredient Name	CAS #	LC50 Rat (4hr)	LD50 Rat
Ethylene Glycol	107-21-1	Not Available	4700 mg/kg
Octylphenoxypoly (ethoxy) ethanol	9036-19-5	Not Available	Not Available

**BURNT RED**

Ingredient Name	CAS #	LC50 Rat (4hr)	LD50 Rat
Ethylene Glycol	107-21-1	Not Available	4700 mg/kg
Octylphenoxypoly (ethoxy) ethanol	9036-19-5	Not Available	Not Available
Talc	14807-96-6	Not Available	Not Available

**EARTH BROWN**

Ingredient Name	CAS #	LC50 Rat (4hr)	LD50 Rat
Ethylene Glycol	107-21-1	Not Available	4700 mg/kg
Octylphenoxypoly (ethoxy) ethanol	9036-19-5	Not Available	Not Available
Talc	14807-96-6	Not Available	Not Available
Titanium Dioxide	13463-67-7	Not Available	Not Available
Carbon Black	1333-86-4	Not Available	Not Available

**RAMBLING ROSE**

Ingredient Name	CAS #	LC50 Rat (4hr)	LD50 Rat
Ethylene Glycol	107-21-1	Not Available	4700 mg/kg
Octylphenoxypoly (ethoxy) ethanol	9036-19-5	Not Available	Not Available
Talc	14807-96-6	Not Available	Not Available

**SUNRISE YELLOW**

Ingredient Name	CAS #	LC50 Rat (4hr)	LD50 Rat
Ethylene Glycol	107-21-1	Not Available	4700 mg/kg
Octylphenoxypoly (ethoxy) ethanol	9036-19-5	Not Available	Not Available
Talc	14807-96-6	Not Available	Not Available

**LEMON YELLOW**

Ingredient Name	CAS #	LC50 Rat (4hr)	LD50 Rat
Ethylene Glycol	107-21-1	Not Available	4700 mg/kg
Octylphenoxypoly (ethoxy) ethanol	9036-19-5	Not Available	Not Available
Talc	14807-96-6	Not Available	Not Available
Quartz	14808-60-7	Not Available	Not Available

**SIREN RED**

Ingredient Name	CAS #	LC50 Rat (4hr)	LD50 Rat
Ethylene Glycol	107-21-1	Not Available	4700 mg/kg
Octylphenoxypoly (ethoxy) ethanol	9036-19-5	Not Available	Not Available

<i>Siren Red (Cont'd)</i>			
Talc	14807-96-6	Not Available	Not Available

---

**SECTION 12: ECOLOGICAL INFORMATION**

**ECOTOXICOLOGICAL INFORMATION:** No Data Available

---

**SECTION 13: DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL METHOD:** Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

---

**SECTION 14: TRANSPORTATION INFORMATION**

**US GROUND (DOT):** Not regulated for Transportation.

**DOT (Department of Transportation):** Hazardous Substances & Reportable Quantities Ethylene glycol 5000 lb (2268 kg) RQ.

**CANADA (TDG):** Not regulated for Transportation.

**IMO:** Not regulated for Transportation.

---

**SECTION 15: REGULATORY INFORMATION**

**SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION:**

Color	CAS #	Chemical Compound	% by WT.	% Element.
Chocolate Brown	107-21-1	Ethylene Glycol	16	-
Midnight Black	107-21-1	Ethylene Glycol	25	-
Exotic Blue	107-21-1	Ethylene Glycol	23	-
Forest Green	107-21-1	Ethylene Glycol	24	-
Winter White	107-21-1	Ethylene Glycol	15	-
Golden Yellow	107-21-1	Ethylene Glycol	12	-
Burnt Red	107-21-1	Ethylene Glycol	14	-
Earth Brown	107-21-1	Ethylene Glycol	25	-
Earth Brown		Manganese Compound	1	1.0
Rambling Rose	107-21-1	Ethylene Glycol	27	-
Sunrise Yellow	107-21-1	Ethylene Glycol	20	-
Lemon Yellow	107-21-1	Ethylene Glycol	20	-
Siren Red	107-21-1	Ethylene Glycol	31	-

**CALIFORNIA PROPOSITION 65:** WARNING: This product contains chemicals know to the State of California to cause cancer and birth defects or other reproductive harm.

**TSCA CERTIFICATION:** All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

---

**SECTION 16: OTHER INFORMATION**

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

Tuscan Stoneworx, LLC, nor any of its affiliates shall be responsible for the use of the information, product, method, or apparatus presented in this Material Safety Data Sheet. The user shall make its own

determination as to its suitability and completeness for its particular use, for the protection of the environment, and health and safety purposes. The user assumes all the risks of relying on this information. In no event shall Tuscan Stoneworx be responsible for damages of any nature whatsoever resulting from the use of or reliance upon this information. By providing this information, Tuscan Stoneworx neither can nor intends to control the method of manner by which the product is used, handled, stored, or transported. Nothing herein shall be construed as a recommendation or license to use any information that conflicts with any patent, trademark or copyright.

TUSCAN STONEWORX, LLC MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE REGARDING THIS INFORMATION, AND NOTHING HEREIN WAIVES ANY CONDITIONS OF SALE. This information could include technical inaccuracies and typographical errors. Content may be modified at any time to the information in this MSDS; these changes will be incorporated into future revisions of the document.

Tuscan Stoneworx  
165 North 1330 West, Suite C-4 | Orem, Utah 84057  
P: (888) 368-9494 F: (801) 734-6959  
[www.tuscanstoneworx.com](http://www.tuscanstoneworx.com)

